

Steel FloorTag™

Fused polyester coated steel

- Mount on warehouse floor to identify locations where rack mount of labels is not feasible.
- Generous barcode X dimensions and extended bar heights enhance functionality and facilitate angular approach scans.
- Durable enough to endure typical forklift warehouse traffic.
- Low density code for convenient scanning by operator seated on forklift or otherwise at a distance from the label.



FEATURES

- Rugged construction resists most traffic in forklift operation environments.

Conforms to Industry Standards:

MIL-DTL-15024F

ISO 15416

ANSI-X3.182-1990

as well as other applicable standards.

BARCODES

- Imaged with Code 39, Datamatrix, or other barcode symbology if desired.
- Variable data can be generated from any sequence you specify or in the case of complex or random data you may provide an electronic data file.
- Our rigorous Quality Management System and robust data management services ensure data integrity and complete delivery.

MATERIALS

- Multilayer polyester fused to .036" thick hot rolled steel backing.
- Adhere to floor with 2-part epoxy.
- Available in a variety of sizes - 6" x 4" is a common standard.

800.382.2323 (toll free)

858.549.8708

858.549.9828

Mail@ExpressCorp.com

ISO 9001:2008 Certified - ITAR Registered

Member: Automatic Identification Manufacturers Association

Member: AIM UID Supplier Alliance

Member: National Assn. of Graphic Identification Product Manufacturers

Member: Specialty Graphic Imaging Association

9155 Trade Place, San Diego, CA 92126 | ExpressCorp.com

